

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number  
**WO 2005/090770 A1**

(51) International Patent Classification<sup>7</sup>: **F02G 1/044,**  
1/057

(21) International Application Number:  
PCT/HR2005/000011

(22) International Filing Date: 3 February 2005 (03.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
P20040269A 19 March 2004 (19.03.2004) HR

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: MIROSLAV, Rak [HR/HR]; Sandora Petefija  
176, 31000 Osijek (HR).


Published:

— with international search report

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: THERMAL HYDRO-MACHINE ON HOT GAS WITH RECIRCULATION



(57) Abstract: The thermal hydro-machine on hot gas with recirculation (Figures 3, 4 and 5) belongs to the group of multi-cylinder piston rotational machines for converting the heat into the mechanical work. The heat is conducted to on the outer side of one part of rotational tubular heat exchanger (1) and is simultaneously conducted away from the other part of same exchanger (1). The exchanger is composed of a set of independent segment collectors (1) arranged in the form of a cylindrical shell, made pair wise with a set of independent segment cylinders with free pistons (2) in which there is the independent gas under pressure. In collectors (1) and cylinders (2) the independent working gas accomplishes a set of simultaneous, successively repeating, thermodynamic cycles (Figures 1 and 2), which states are determined by the position

with respect to the heat source or cooled space, where the isothermal expansion and compression are predominant. Simultaneously, at shorter nonisothermal state changes, the heat self-regenerates at a greatest deal without the additional characteristic assemblies, which substituting function is taken over by the existing elements, so that the number of assemblies is maximally reduced. The relatively slower opposite turning of assembly I (1, 2, 3, 4, 5, 6 and 7) with respect to working assembly 11 (8, 9 and 10) is achieved by a system of coupled mechanical transmitters (7, 10 and 11), enabling the transmitting of the exchanger across the heat source or the cooled space. By introducing the recirculation medium, which via the pistons accepts the pressure work and by means of the system of directed (3) and return channels (4 and 5) converts the hydrodynamic energy of the flow into the actuating of turbine (8) and shaft (9), the continued adjustable catalytic connection between a set of integral expansions and compressions is achieved, accomplishing the isothermal continuity. By means of this type construction the heat is continuously, uniformly and directly converted into the rotational mechanical work in a simplest way, by the intensity as it arrives and at the best effect.